CONTROL4 WIRELESS SWITCH, CONTEMPORARY



CONTROL4® C4-SW120277-C, C4-SW240-C

Control4's new Contemporary Lighting is designed to elevate lighting control and aesthetics. With a beautiful design that suits the smart home of today, Contemporary Lighting gives you a new industrial design that customers will love.

Get on/off control for virtually every type of load, including LED lights, incandescents, halogens, electronic low-voltage (solid-state) transformers, magnetic (iron core) low-voltage transformers, fluorescents, compact fluorescents, and motors, including ceiling fans and bathroom ventilation fans. The Wireless Switch also handles high in-rush loads such as fountain pumps or large banks of fluorescent lights and can be used to switch wall outlets. Available in 10 stylish colors and finishes. 120V/277V or 240V.

Faceplates are not included—remember to order faceplates separately.

- Compatible with a variety of load types including incandescent, halogen, electronic low-voltage (solid state) transformers, magnetic (iron core) low-voltage transformers, fluorescents, compact fluorescents, LEDs, and motors
- Continuously measures energy being used by the attached load
- Elegant, sophisticated design makes a beautiful addition to any home or business
- Custom engraving available to clearly identify which light each switch controls
- Backlit button engraving with programmable color control for easy readability regardless of time of day or light level
- Programmable RGB LEDs provide status feedback for lighting and other devices in the system
- Ambient light sensor automatically adjusts backlight and status LED brightness depending on the light level in the room
- Available in a wide array of gloss and satin colors (see Available Colors)
- Control4 screw-less faceplates, sold separately, provide a sleek profile (see Available Accessories)



CONTROL4 WIRELESS SWITCH, CONTEMPORARY

SPECIFICATIONS

Model number C4-SW120277-C and C4-SW240-C

Power requirements | C4-SW120277-C: 110-277VAC +/-10%, 50/60 Hz

C4-SW240-C: 220VAC-240VAC +/-10%, 50/60 Hz

This device requires a neutral connection.

Power consumption | 120V: 400mW

240V: 950mW 277: 1150mW

Control communications | Zigbee, IEEE 802.15.4, 2.4 GHz, 15-channel, spread-spectrum

Load types/ratings

Supported load types | Incandescent, halogen, electronic (solid state)

low-voltage (ELV) transformers, magnetic (iron core, inductive) low-voltage (MLV) transformers, fluorescents,

compact fluorescents, LEDs, motors

Maximum load | 120V: 15A, 1/2 HP

277V: 8A, 1/2 HP 240V: 10A, 1/2 HP

Mechanical and Environmental

Weight | 0.5 kg (0.12 lb)

Shipping weight | 0.08 kg (0.18 lb)

Wall box volume | 94.2 cubic cm (5.75 cubic in.)

Operating temperature 0 to 40 °C (32 to 104 °F)

Storage temperature | -20 to 70 °C (-4 to 158 °F)

Humidity 5% to 95% non-condensing

Available colors

C4-SW120277-C | AU, BI, BL, BR, GR, IV, LA, MB, SW, WH

C4-SW240-C AU, BI, BL, MB, SW, WH

Available accessories

Faceplate, 1 Gang (C4-FP1-xx) AU, BI, BL, BR, CH*, GR, IV, LA, MB, MS*, SN*, SW, WH, VB*

Faceplate, 2 Gang (C4-FP2-xx) AU, BI, BL, BR, GR, IV, LA, MB, MS*, SN*, SW, WH, VB*

Faceplate, 3 Gang (C4-FP3-xx) AU, BI, BL, BR, GR, IV, LA, MB, MS*, SN*, SW, WH, VB*

Faceplate, 4 Gang (C4-FP4-xx) AU, BI, BL, BR, GR, IV, LA, MB, MS*, SN*, SW, WH, VB*

Color Kit (C4-CKFPDAPD-xx) | AU, BI, BL, BR, GR, IV, LA, MB, SW, WH

Engraved Button, Rocker AU, BI, BL, BR, GR, IV, LA, MB, SW, WH

(C4-EBDR-xx)

Gloss colors: BL=Black, BR=Brown, GR=Gray, IV=Ivory, LA=Light Almond, WH=White Satin colors: AU=Aluminum, BI=Biscuit, MB=Midnight Black, SW=Snow White Metal finishes: CH=Chrome, MS=Matte Stainless, SN=Satin Nickel, VB=Venetian Bronze

*Coming soon

MORE INFO

Find details of the product's Limited Warranty at

snapav.com/warranty

or request a paper copy from Customer Service

at 866.424.4489.

Find other legal resources, such as regulatory notices and patent information, at snapav.com/legal.

MOST RECENT DATA SHEET REVISION



NOVI/OTTV INCTALLATION CUIDE



240V INSTALLATION GUIDE



