



Highlights:

- 2-way in-wall loudspeaker system designed for off-axis listening as LCR and surround channels
- 1-inch 2410H-2 compression driver tweeter mated to a JBL patented High-Definition Imaging (HDI™) horn precision molded baffle assembly
- Two 5.25-inch (130mm) Advanced Aluminum Matrix cone cast frame woofers
- Can be mounted vertically or horizontally
- Patented Cat Claw installation mechanism
- Gold plated, spring-loaded binding posts
- Includes paintable zero-bezel, magnetically attached grilles
- · Compatible with WB52 pre-construction bracket

General Specifications:

- ► Type: 2-way in-wall loudspeaker
- ► Low Frequency Driver: Two 5.25" (130mm) advanced Aluminum Matrix cone cast-frame woofers (JW13AI-4)
- ► High Frequency Driver: 1" (25mm) 2410H-2 Teonex® annular ring-diaphragm compression driver
- ► Recommended Amplifier Power: 25 150W RMS
- ► Impedance: 4 Ohm
- ► Loudspeaker Sensitivity: 88dB/2.83V/1m
- ► Frequency Response: 55Hz 30kHz (-6dB on-axis), 2pi anechoic
- ► Crossover Frequency: 2.0kHz
- ► High Frequency Coverage Angle (-6dB): 60° Vertical, 90° Horizontal (Left: 30°, Right: 60°, from center line), from 2kHz to 15kHz
- ► Enclosure Type: Open back
- ► Controls: Boundary Proximity Control
- ► Grille Dimensions: 7.32" (186mm) x 19.15" (486mm)
- ► Product Dimensions (with grille): 7.32" (186mm) x 19.15" (486mm) x 3.88" (99mm)
- Cut-out Dimensions: 5.94" (151mm) x 17.80" (452mm)
- ► Rough-in Bracket: WB52
- ► Mounting Depth: 3.64" (93mm)
- ► Input Type: Gold-plated spring-loaded binding posts
- ► Product Weight: 12.6 lbs (5.72kg)
- ► Shipping Weight: 14.6 lbs (6.62kg)
- ► Shipping Units of Measure: Each
- ▶ Warranty: 5 Years





